

**Description:** HDPC Dryback Plank flooring is produced using Wellmade's patented (China) Pat, Pending (USA) High Density Plastic Composite Core (HDPC®). HDPC Dryback Plank flooring also exceeds the performance of standard vinyl flooring and is Greenguard Gold certified which enhances LEED credits. Our HDPC core remains stable and performs on any level of the home or office.

**Construction:** Co-Extruded PVC (film, core, backer)

**Dimensions:** 2mm-12mil/2mm X 6.22" X 48.03"  
3mm- 20mil/3mm x 6.14" x 48.03"

**Installation:** Glue down

**Packaging:** 2mm- 14 pcs/box=29.05sf  
3mm- 18 pcs/box, 36.88sf

**Warranty:** 2mm- 20 year residential / 3 year light commercial  
3mm- Lifetime residential / 15 year light commercial

<b>Testing:</b>	<b>ASTM E90-2009/ASTM E413-10</b>	STC	62
	<b>ASTM E492-09/ASTM E989-12</b>	IIC	53
	<b>ASTM E2179-2003/ASTM E989-12</b>	Delta	3
	<b>ISO 4918:2009</b>	Caster Chair (25000r)	Pass
	<b>Phthalates</b>		ND (Not Detected)
	<b>ASTM F2055-17</b>	Size, tolerance	
		Length	-0.50mm
		Width	0.01mm
	<b>ASTM F386-17</b>	Thickness, product-tolerance	0.09mm
	<b>ASTM F410-08</b>	Thickness, wear layer-tolerance	0.00mm
	<b>ASTM F2055-17</b>	Squareness-average	0.03mm
	<b>ASTM F1914-17</b>	Residual indentation-average	1.5%
	<b>ASTM F137-08(2013)</b>	Flexibility	No crack/No break
	<b>ASTM F2199-09</b>	Dimensional Stability	
		Length	-0.07%
	Width	0.03%	
<b>ASTM F925-13</b>	Resistance to chemicals	No change	
<b>ASTM F1515-15</b>	Resistance to light	Pass	
<b>ASTM F1514-03(2013)</b>	Resistance to heat	Pass	

**Country of Origin:** Made in China